

PTO/SB/05 (12/97)

Please type a plus sign (+) inside this box 

Approved for use through 09/30/00. OMB 0651-0032

Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

## UTILITY PATENT APPLICATION **TRANSMITTAL**

BA-22580 Attorney Docket No.

Total Pages

First Named Inventor or Application Identifier

HIROSHI HASEGAWA,

(Only for new nonprovisional applications under 37 CFR 1.53(b))

EM564188157US Express Mail Label No.

	PLICATION ELEMENTS  er 600 concerning utility patent application of	contents.	Assistant Commissioner for Patents  ADDRESS TO: Box Patent Application Washington, DC 20231								
1. X (Subi	Transmittal Form mit an onginal, and a duplicate for fee proce		Microfiche Computer Program (Appendix)     Nucleotide and/or Amino Acid Sequence Submission								
	erred arrangement set forth below)	37 ]1	(if applicable, all necessary)								
	scriptive title of the Invention		a. Computer Readable Copy								
	oss References to Related Application: Itement Regarding Fed sponsored R &		D C (ideathical to computes comp								
	tement Regarding Fed Sponsored R & ference to Microfiche Appendix		<u> </u>								
	ckground of the Invention		c. Statement verifying identity of above co	pies							
- Brid	ef Summary of the Invention		ACCOMPANYING APPLICATION PARTS								
- Bri	ef Description of the Drawings (if filed)	1									
- De	tailed Description		8. X Assignment Papers (cover sheet & document	(s))							
	aim(s)		9. 37 CFR 3.73(b) Statement (when there is an assignee) Power of	Attorney							
	stract of the Disclosure	,	10. English Translation Document (if applicable)	ļ							
4 Oath or De	wing(s) (35 USC 113) [Total Sheets claration [Total Pages		Information Disclosure Copies of Statement (IDS)/PTO-1449 Citations	IDS							
	Newly executed (original or copy)	'	12. Preliminary Amendment								
a. [	Copy from a prior application (37)		Return Receipt Postcard (MPEP 503)								
b	(for continuation/divisional with Box 17)	' completed)	(Should be specifically itemized)								
	[Note Box 5 below DELETION OF INVENTOR(S	2)	Small Entity Statement filed in prior application								
	Signed statement attache		Statement(s) Status still proper and de	JI CU							
	inventor(s) named in the pri see 37 CFR 1.63(d)(2) and		(if foreign priority is daimed)								
	rporation By Reference (useable if Box	4b is checked)	16 Other								
	entire disclosure of the prior application of the oath or declaration is supplied										
is co	onsidered as being part of the disclosi	ure of the		••							
	ompanying application and is hereby in trence therein.	ncorporated by									
	TINUING APPLICATION, check appr	opriate box and	supply the requisite information:								
		nuation-in-part (Cli	00 / 520 001								
	18. CO	RRESPONDE	NCE ADDRESS								
Custom	ner Number or Bar Code Label (Insert Cu	stomer No. or Atta	or Correspondence address b	elow							
	BUCKNAM AND A	RCHER									
NAME	DOORNALI KIND K										
	600 OLD COUNT	'RY ROAD									
ADDRESS	OUG OHD GOOM!	TI KOND									
CITY	GARDEN CITY	STATE	NEW YORK ZIP CODE 11530								
COUNTRY	U.S.A.	TELEPHONE	(516)222-8885 FAX (516)222-0	)135							
	U.D.A.		(JEO/ALA OOOJ   [(JEO/ALA-)	2000 Anv							

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual of comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231 DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

Approved for use through 09/30/00. OM8 0651-0032

Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

## FEE TRANSMITTAL

Note: Effective October 1, 1997. Patent fees are subject to annual revision.

TOTAL AMOUNT OF PAYMENT (\$) 1,982.00

	The state of the s
Comple	te if Known
Application Number	
Filing Date	
First Named Inventor	HIROSHI HASEGAWA
Group Art Unit	
Examiner Name	
Attorney Docket Number	BA = 22580

METHOD OF PAYMENT (check one)	FEE CALCULATION (continued)							
The Commissioner is hereby authorized to charge indicated foos and credit any over payments to:  Deposit	3. AD Large I Fee Code	Entity Fee	Sma Fee	AL FE	ES	Fee Paid		
Account Number	105	130	205	65	Surcharge - late filing fee or oath			
Deposit Account Name	127	50	227	25	Surcharge - late provisional filing fee or cover sheet.			
Charge Any Additional Fee Required Under 37 CFR 1.18 at the Mailing of the	139	130	139	130	Non-English specification			
37 CFR 1.16 and 1.17 Notice of Allowance	147 2	520	147	2,520	For filing a request for reexamination			
2. X Payment Enclosed;	112	920*	112	920*	Requesting publication of SIR prior to Examiner action			
Check Money Other	113 1,	.840°	113	1,840*	Roquesting publication of SIR after Examiner action			
FEE CALCULATION	115	110	215	55	Extension for reply within first month			
	116	400	216	200	Extension for reply within second month			
1. FILING FEE	117	950	217	475	Extension for reply within third month			
Large Entity Small Entity	118 1,	510	218	755	Extension for reply within fourth month			
Fee Fee Fee Fee Description Fee Paid Code (\$) Code (\$)	128 2,	060	228	1,030	Extension for raply within fifth manth			
101 790 201 395 Utility filing foe 790.	119	310	219	155	Notice of Appeal			
106 330 206 165 Design filing fee	120 3	310	220	155	Filing a brief in support of an appeal			
107 540 207 270 Plant filing fee	121 2	270	221	135	Request for oral hearing			
108 790 208 395 Reissue filing foo	138 1,	510	138 '	1,510	Petition to institute a public use proceeding			
114 150 214 75 Provisional filling fee	140	110	240	55	Petition to revive - unavoidable			
SUBTOTAL (1) (\$) 790.	141 1,	320	241	680	Petition to revive - unintontional			
	142 1,	320	242	660	Utility issue fee (or reissue)			
2. CLAIMS Extra Fee from Fee Paid	143	150	243	225	Design issue fee			
Total Claims   22 -20 =   2 x 22 =   44	144 6	<b>370</b>	244	335	Plant issue fee			
Independent 17 -3 = 14 x 82 = 1148.	122 1	130	122	130	Petitions to the Commissioner			
Multiple Dependent Claims X =	123	50	123	50	Petitions related to provisional applications			
Large Entity Small Entity	126 2	40	126	240	Submission of Information Disclosure Stmt			
Fee Foo Fee Fee Fee Description Code (\$) Code (\$)	581	40	581	40	Recording each patent assignment per property (times number of properties)			
103 22 203 11 Claims in excess of 20	146 7	<b>'90</b>	246	39\$	Filing a submission after final rejection			
102 82 202 41 Independent claims in excess of 3					(37 CFR 1.129(a))			
104 270 204 135 Multiple dependent claim	149 7	90	249	395	For each additional invention to be examined (37 CFR 1.129(b))			
109 82 209 41 Reissus Independent claims over original patent	Otner foo	(spe	cifv)		axananad (57 CFR 1.123(5))			
110 22 210 11 Reissue claims in excess of 20 and over ongleal patent					}			
	Other fe	u (spe	ecify)			} ]		
SUBTOTAL (2) (\$)1,192.	Reduc	ed by	Basi	: Filing I	Fee Paid SUBTOTAL (3) (\$)			

SUBMITTED B	Y			Complete (if	applicable)
Printed Name	FERNANDA M. FIORDALISI			Reg. Number	20,938
Signature	Fer H Fiond	Date	4/9/98	Deposit Account User ID	

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will very depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patont and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissionar for Patonts.

This application is a Continuation-in-part of U.S. Serial No. 08/539,001 filed on October 4, 1995.

# FLUID COMPOSITIONS CONTAINING REFRIGERATOR OILS AND CHLORINE-FREE FLUOROCARBON REFRIGERANTS

5

10

15

20

25

#### Background of the Invention

#### 1. Field of the Invention

This invention relates to a fluid composition for compressors of refrigerators comprising a chlorine-free fluorocarbon as a refrigerant and a lubricating oil (the oil being hereinafter referred to as "a refrigerator oil for use with a chlorine-free fluorocarbon refrigerant") and, more specifically, it relates to such a fluid composition which comprises a specific ester as a base oil and is superior in various properties.

#### 2. Prior Art

Generally, naphthenic mineral oils, paraffinic mineral oils, alkylbenzenes, polyglycolic oils, ester oils and mixtures thereof, which have each a kinematic viscosity of 10 - 200 cSt at  $40^{\circ}$ C, as well as these oils incorporated with suitable additives have been used as refrigerator oils.

On the other hand, chlorofluorocarbons (CFCS) type refrigerants, such as CFC-11, CFC-12, CFC-113 and HCFC-22, have been used for refrigerators.

Of these CFCS, CFCS such as CFC-11, CFC-12 and CFC-113, which are obtained by substituting all the hydrogen

10

15

20

25

atoms of hydrocarbons thereof by halogen atoms including chlorine atoms, may lead to the destruction of the ozone layer, and therefore, the use of the CFCS has been controlled. Accordingly, chlorine-free fluorocarbons, such as HFC-134a and HFC-152a, have been being used as substitutes for CFCS. HFC-134a is especially promising as a substitute refrigerant since it is similar in thermodynamic properties to CFC-12 which has heretofore been used in many kinds of refrigerators of home cold-storage chests, airconditioners and the like.

Refrigerator oils require various properties, among which their compatibility with refrigerants is extremely important in regard to lubricity and system efficiency in refrigerators. However, conventional refrigerator oils comprising, as the base oils, naphthenic oils, paraffinic oils, alkylbenzenes, heretofore known ester oils and the like, are hardly compatible with chlorine-free fluorocarbons such as HFC-134a. Therefore, if said conventional refrigerator oils are used in combination with HFC-134a, the resulting mixture will separate into two layers at normal temperature so as to degrade the oil-returnability which is the most important within the refrigeration system and cause various troubles such as a decrease in refrigeration efficiency, the deterioration of lubricity and the consequent seizure of the compressor within the system whereby the refrigerator oils are made unsuitable for use as such. In addition, polyglycolic oils are also known as

10

15

20

25

refrigerator oils for their high viscosity index and are disclosed in, for example, JP-A-57-42119 and JP-A-61-52880 and JP-A-57-51795. However, the polyglycolic oils disclosed in these prior art publications are not fully compatible with HFC-134a thereby raising the same problems as above and rendering them unusable.

Further, US-A-4,755,316 discloses polyglycolic refrigerator oils which are compatible with HFC-134a and US-A-4,851,144 discloses refrigerator oils comprising a mixture of an ester and a polyglycol which are compatible with HFC-134a. In addition, the present inventors developed polyglycolic refrigerator oils which have excellent compatibility with HFC-134a as compared with conventional known refrigerator oils, filed an application for a patent for the thus developed polyglycolic refrigerator oils and have already obtained a patent (US-A-4,948,525) therefor. It has been found, however, that the polyglycolic oils raise problems as to their high compatibility with water and inferior electrical insulating property.

On the other hand, refrigerator oils used in compressors of home refrigerators and the like are required to have a high electrical insulating property. Among the known refrigerator oils, alkylbenzenes and the mineral oils have the highest insulating property, but they are hardly compatible with chlorine-free fluorocarbons such as HFC-134a as mentioned above. WO 90/12849 describes a composition comprising a hydrogen-containing halogenocarbon and a

specific ester lubricant. No refrigerator oil having both high compatibility with chlorine-free fluorocarbons such as HFC-134a and a high insulating property has been developed prior to the present invention.

5

#### Summary of the Invention

The present inventors made various intensive studies in attempts to develop refrigerator oils which can meet the aforesaid requirements and, as the result of their studies, they found that esters having specific structures have excellent compatibility with chlorine-free fluorocarbons such as HFC-134a, a high electrical insulating property, and a low pour point as well as excellent lubricity. The present invention is based on this finding.

15

10

The object of the present invention is to provide fluid compositions comprising a refrigerator oil and a chlorine-free fluorocarbon refrigerant, the oil comprising as a major component (or a base oil) an tetraester having a specific structure and having excellent compatibility with chlorine-free fluorocarbons such as HFC-134a, high electrical insulating property, high wear resistance, low hygroscopicity, and high thermal and chemical stability.

25

20

The present invention provides a fluid composition for a refrigerator, which comprises a chlorine-free fluorocarbon refrigerant and a refrigerator oil, said

10

15

20

25

refrigerator oil consisting essentially of a tetraester of pentaerythritol of formula (1)

$$\begin{array}{c} CH_2OH \\ HOH_2C - \overset{|}{C} - CH_2OH \\ CH_2OH \end{array} \tag{1}$$

with both 2-ethylhexanoic acid and 3,5,5-trimethylhexanoic acid.

The tetraester products obtained by any conventional methods may be refined to remove the by-products and/or unreacted reactants, but the by-products and/or unreacted reactants may be present in small amounts in the refrigerator oils according to the present invention as far as they do not impair the excellent performances thereof.

In the preparation of the refrigerator oil according to the present invention, the ester mentioned above may be used singly, or jointly as a mixture of at least one kind of other esters for adding to the base oil.

The kinematic viscosities of the base oil according to the present invention are in the range of preferably 2-150 cSt, more preferably 5-100 cSt at  $100^{\circ}$ C.

The refrigerator oil according to the present invention may contain as the only base oil the tetraester of pentaerithritol with both 2-ethylhexanoic acid and 3.5.5-trimethylhexanoic acid and, as required, it may be incorporated with paraffinic mineral oils, naphthenic mineral oils, poly $\alpha$ -olefins, alkylbenzenes and the like,

10

15

20

25

but, in this case, the resulting mixed oil will be lowered in compatibility with hydrogen-containing halogonocarbons.

The amount of these conventional oils so incorporated is not particularly limited as far as the excellent performances of the refrigerator oil according to the present invention are not impaired, but the tetraester of pentaerythritol with both 2-ethylhexanoic acid and 3,5,5-trimethylhexanoic acid should be present in the resulting mixed oil in a ratio of usually more than 50 % by weight, preferably not less than 70 % by weight of the total amount of the mixed oil.

To further improve the refrigerator oil according to the present invention in thermal stability and chemical stability, it is incorporated with at least one kind of an epoxy compound. The epoxy compound used herein is preferably selected from the group consisting of phenylglycidyl ether epoxy compounds, alkylglycidyl ether epoxy compounds, alkylglycidyl ether epoxy compounds, aryloxirane compounds, alkyloxirane compounds, alicyclic epoxy compounds, epoxidized fatty acid monoesters and epoxidized vegetable oils.

The said phenylglycidyl ether epoxy compounds used herein include phenylglycidyl ether and derivatives thereof such as alkylphenylglycidyl ethers. The said alkylphenylglycidyl ethers are those having 1 to 3 alkyl groups having 1 to 13 carbon atoms, among which are preferred those having an alkyl group having 4 to 10 carbon

10

1.5

20

atoms, such as n-butylphenylglycidyl ether, i-butylphenylglycidyl ether, sec-butylphenylglycidyl ether, tert-butylphenylglycidyl ether, pentylphenylglycidyl ether, hexylphenylglycidyl ether, heptylphenylglycidyl ether, octylphenylglycidyl ether, nonylphenylglycidyl ether and decylphenylglycidyl ether.

The alkylglycidyl ether epoxy compounds include decylglycidyl ether, undecylglycidyl ether, dodecylglycidyl ether, tridecylglycidyl ether, tetradecylglycidyl ether, 2-ethylhexylglycidyl ether, neopentyl glycol diglycidyl ether, trimethylolpropane triglycidyl ether, pentaerythritol tetraglycidyl ether, 1,6-hexanediol diglycidyl ether, sorbitol polyglycidyl ether, polyalkylene glycol monoglycidyl ethers and polyalkylene glycol diglycidyl ethers.

The glycidyl ester epoxy compounds include phenylglycidyl esters, alkylglycidyl esters and alkenylglycidyl esters with glycidyl 2,2-dimethyl octanoate, glycidyl benzoate, glycidyl acrylate, glycidyl methacrylate and the like being preferred.

The aryloxirane compounds include 1,2-epoxystyrene and alkyl-1,2-epoxystyrene.

The alkyloxirane compounds include 1,2-epoxybutane,
1,2-epoxypentane, 1,2-epoxyhexane, 1,2-epoxyheptane, 1,2epoxyoctane, 1,2-epoxynonane, 1,2-epoxydecane, 1,2epoxyundecane, 1,2-epoxydodecane, 1,2-epoxytridecane, 1,2epoxytetradecane, 1,2-epoxypentadecane, 1,2-epoxyhexadecane,

20

1,2-epoxyheptadecane, 1,1,2-epoxyoctadecane, 2-epoxynonadecane and 1,2-epoxyeicosane.

epoxycyclohexane, 1,2-epoxycyclopentane, 3,4
5 epoxycyclohexylmethyl-3,4-epoxycyclohexane carboxylate, bis
(3,4-epoxycyclohexylmethyl) adipate, exo-2,3epoxynorbornane, bis (3,4-epoxy-6-methylcyclohexylmethyl)
adipate, 2-(7-oxabicyclo[4.1.0]hept-3-yl)-spiro(1,3-dioxane5,3'-[7]oxabicyclo[4.1.0]heptane, 4-(1'-methylepoxyethyl)10 1,2-epoxy-2-methylcyclohexane and 4-epoxyethyl-1,2epoxycyclohexane.

The alicyclic epoxy compounds include 1,2-

The epoxidized fatty acid monoesters include esters of an epoxidized fatty acid having 12 to 20 carbon atoms and an alcohol having 1 to 8 carbon atoms, phenol or an alkylphenol. In particular, butyl, hexyl, benzyl, cyclohexyl, methoxyethyl, octyl, phenyl or butylphenyl esters of epoxidized stearic acid may preferably be used.

The epoxidized vegetable oils include epoxidized compounds of vegetable oils such as soybean oil, linseed oil and cottonseed oil.

Among these epoxy compounds, the preferable ones include phenylglycidyl ether epoxy compounds, alkylglycidyl ether epoxy compounds alkylglycidyl ether epoxy compounds and alicyclic epoxy compounds.

It is desirable that these epoxy compounds be incorporated in the refrigerator oil according to the present invention in a ratio of 0.1-5.0% by weight,

10

15

20

preferably 0.2-2.0% by weight, of the total amount of the refrigerator oil.

The refrigerator oil composition according to the present invention may be incorporated further with at least one kind of a phosphorus compound selected from the group consisting of phosphoric esters, acid phosphoric esters, amine salts of acid phosphoric esters, chlorinated phosphoric esters and phosphorous esters, to improve the oil composition in wear resistance and load resistance. phosphorus compounds are esters of phosphoric acid or phosphorous acid and an alkanol or a polyether type alcohol, or derivatives of the esters. The phosphoric esters are exemplified by tributyl phosphate, triphenyl phosphate and tricresyl phosphate. The acid phosphoric esters are exemplified by ditetradecyl acid phosphate, dipentadecyl acid phosphate, dihexadecyl acid phosphate, diheptadecyl acid phosphate and dioctadecyl acid phosphate. salts of acid phosphoric esters are exemplified by salts of the above acid phosphoric esters and amines such as methylamine, ethylamine, propylamine, butylamine, pentylamine, hexylamine, heptylamine, octylamine, dimethylamine, diethylamine, dipropylamine, dibutylamine, dipentylamine, dihexylamine, diheptylamine, dioctylamine, trimethylamine, triethylamine, tripropylamine,

tributylamine, tripentylamine, trihexylamine, triheptylamine and trioctylamine. The chlorinated phosphoric esters are exemplified by tris-dichloropropyl phosphate.

1.0

15

20

25

tris chloroethyl phosphate,

polyoxyalkylene bis[di(chloroalkyl)] phosphate and tris chlorophenyl phosphate. The phosphorous esters are exemplified by dibutyl phosphite, tributyl phosphite,

dipentyl phosphite, tripentyl phosphite, dihexyl phosphite, trihexyl phosphite, diheptyl phosphite, triheptyl phosphite, dioctyl phosphite, trioctyl phosphite, dinonyl phosphite, didecyl phosphite, diundecyl phosphite, triundecyl phosphite, didodecyl phosphite, tridodecyl phosphite,

diphenyl phosphite, triphenyl phosphite, dicresyl phosphite, tricresyl phosphite and mixtures thereof. These phosphorus compounds may be added to the refrigerator oil in a ratio of 0.1-5.0 % by weight, preferably 0.2-2.0 % by weight, of the total amount of the refrigerator oil.

Of course, both of the aforementioned phosphorus compounds and epoxy compounds may be used jointly.

To further enhance the refrigerator oil according to the present invention in performances, the refrigerator oil may be incorporated, as required, with heretofore known additives for a refrigerator oil, which include phenol-type antioxidants such as di-tert.-butyl-p-cresol and bisphenol A; amine-type antioxidants such as phenyl-α-naphthylamine and N,N-di(2-naphthyl)-p-phenylenediamine; wear resistant additives such as zinc dithiophosphate; extreme pressure agents such as chlorinated paraffin and sulfur compounds; oiliness improvers such as fatty acids; antifoaming agents such as silicone-type ones; and metal inactivators such as

10

15

20

25

benzotriazole. These additives may be used singly or jointly. The total amount of these additives added is ordinarily not more than 10 % by weight, preferably not more than 5 % by weight, of the total amount of the refrigerator oil.

The refrigerator oils according to the present invention consisting essentially of a tetraester of pentaerythritol with both 2-ethylhexanoic acid and 3,5,5trimethylhexanoic acid as the base oil should have such viscosity and pour point as those which are normally suitable for an ordinary refrigerator oil, but they should have a pour point of not higher than  $-10^{0}$ C, preferably  $-20^{0}$ C to  $-80^{\circ}$ C, to prevent them from solidification at a low temperature. Further, they should desirably have a kinematic viscosity of not less than 2cSt, preferably not less than 3cSt at 100°C, to keep the sealability of the compressor when used, while they should desirably have a kinematic viscosity of not more than 150cSt, preferably not more than 100cSt at 100°C, in view of their fluidity at a low temperature and the efficiency of heat exchange in the evaporator when used.

The refrigerants which may be used in refrigerators in which the fluid composition of the present invention are suitably used, include chlorine-free fluorocarbons such as alkane fluorides having 1-3 carbon atoms, preferably 1-2 carbon atoms. The said chlorine-free fluorocarbons are exemplified by HFCs (chlorine-free type halogenocarbons)

10

15

20

25

such as difluoromethane (HFC-32), trifluoromethane (HFC-23), pentafluoroethane (HFC-125), 1,1,2,2-tetrafluoroethane (HFC-134), 1,1,1,2-tetrafluorocthane (HFC-134a), 1,1,1trifluoroethane (HFC-143a), 1,1-difluoroethane (HFC-152a) and mixtures thereof. Among these chlorine-free fluorocarbons, HFC-32, HFC-23, HFC-125, HFC-134, HFC-134a and HFC-152a, are preferable in view of the environmental problems. The refrigerant used may suitably be selected from these halogenocarbons mentioned above depending on the purpose for which the resulting refrigerant is used as well as the properties which are desirable for the resulting refrigerant. The preferable refrigerants are exemplified by HFC-134a; a mixture of HFC-134a (60-80wt%) and HFC-32 (40-20wt%); a mixture of HFC-32 (50-70wt%) and HFC-125 (50-30wt%); a mixture of HFC-134a (60wt%), HFC-32 (30wt%) and HFC-125 (10wt%); a mixture of HFC-134a (52wt%), HFC-32 (23wt%) and HFC-125 (25wt%); and a mixture of HFC-143a

The fluid composition of the present invention for use in a refrigerator is a mixture of the refrigerator oil and a chlorine-free halogenocarbon such as an alkane fluoride as mentioned above.

(52wt%), HFC-125 (44wt%) and HFC-134a (4wt%).

The mixing ratio of the refrigerator oil and the refrigerant in the resulting composition is not particularly limited, but the refrigerator oil is usually comprised in an amount of 1-500 parts by weight, preferably in an amount of

10

15

20

2-400 parts by weight, based on 100 parts by weight of the refrigerant.

The refrigerator oils according to the present invention are very excellent in compatibility with the hydrogen-containing halogenocarbons as compared with the heretofore known refrigerator oils. Further, the refrigerator oils according to the present invention are excellent because they have not only high compatibility with the hydrogen-containing halogenocarbons and high electrical insulating property but also high lubricity, low hygroscopicity, low pour point and high thermal and chemical stability.

The fluid compositions of the present invention may particularly preferably be used in refrigerators, airconditioners, dehumidifiers, cold-storage chests, freezers, freeze and refrigeration warehouses, automatic vending machines, showcases, cooling units in chemical plants, and the like which have a reciprocating or rotary compressor: Further, the above refrigerator oils may also preferably be used in refrigerators having a centrifugal compressor.

The present invention will be better understood by the following Examples and Comparative Examples.

#### Examples 1-2 and Comparative Examples 1-14

First, base oils according to the present invention (Base oil 1) and comparative base oils (Base oils 2-13),

which are used in the Examples and Comparative Examples, respectively, are illustrated as follows:

[Base oil 1] A tetraester of pentaerythritol (1 mol), 2-ethylhexanoic acid (2 mol) and 3,5,5-trimethylhexanoic acid

5 (2 mol) 
$$C = \begin{bmatrix} CH_2 - OOC - R \end{bmatrix}_4 \quad R ; \quad -CH - CH_2 - CH_2 - CH_2 - CH_3 - CH_4 - CH_4 - CH_5 -$$

or
$$CH_3$$
  $CH_3$ 
 $-CH_2 - CH - CH_2 - C - CH_3$ 
 $CH_3$ 

10

[Base oil 2] A tetraester of pentaerythritol (1 mol) and 2-ethylhexanoic acid (4 mol):

$$C = \left[ CH_2 - OOC - R \right]_4$$
  $R : -CH - CH_2 - CH_2 - CH_3 - CH_3$ 

15

[Base oil 3] A tetraester of pentaerythritol (1 mol) and 3,5,5-trimethylhexanoic acid (4 mol):

$$C = \begin{bmatrix} CH_{3} & CH_{3} \\ CH_{2} - OOC - R \end{bmatrix}_{4} \quad R \; ; \; -CH_{2} - CH_{2} - CH_{2} - CH_{3} \\ CH_{3} & CH_{3} \end{bmatrix}$$

20

[Base oil 4] A naphthenic mineral oil

[Base oil 5] A branched-chain type alkylbenzene (average molecular weight: about 300)

25

[Base oil 6] Polyoxypropylene glycol monobutyl ether (average molecular weight: about 500)

[Base oil 7] Polyoxypropylenc glycol monobutyl ether (average molecular weight: about 1000)

[Base oil 8] Polyoxypropylene glycol (average molecular weight: about 700)

[Base oil 9] Polyoxypropylene glycol (average molecular weight: about 2000)

10 [Base oil 10] A tetraester of pentaerythritol (1 mol) and n-nonanoic acid (4 mol):

[Base oil 11] A tetraester of pentaerythritol (1 mol) and coconut oil

15

25

[Base oil 12] A triester of trimethylolpropane (1 mol) and n-nonanoic acid (3 mol):

[Base oil 13] A triester of trimethylolpropane (1 mol) and coconut oil

The refrigerator oils of Examples 1-2 according to the present invention each of which has a composition indicated in the following Table 1 were prepared and then evaluated for their performances that are their miscibility with HFC-134a, insulating property, wear resistance, hygroscopicity and thermal and chemical stability by the

following respective test methods. The results thus obtained are indicated in Table 1.

For comparison, the ester of pentaerithritol with 2-cthylhexanoic acid (Comparative Examples 1 and 2), the ester of pentaerithritol with 3,5,5-trimethylhexanoic acid (Comparative Examples 3 and 4), the mineral oil (Comparative Example 5), the alkylbenzene (Comparative Example 6), the polypropylene glycol monoalkyl ethers (Comparative Examples 7 and 8), the polypropylene glycols (Comparative Examples 9 and 10) and the straight-chain fatty acid esters of polyol alcohols (Comparative Examples 11-14) which have heretofore been used as refrigerator oils were evaluated for their performances in the same manner as in Examples 1-2. The results thus obtained are also indicated in Table 1.

15

20

10

5

#### (Miscibility with HFC-134a)

0.2 g of the test oil of each of the Examples and the Comparative Examples and 1.8 g of the refrigerant (HFC-134a) were sealed in a glass tube having an inner diameter of 6 mm and a length of 220 mm. This glass tube was then placed in a thermostat maintained at a predetermined low temperature or high temperature to observe whether the refrigerant and the test oil were miscible with each other, separated from each other or made white-turbid.

25

(Insulating property)

The test oils were each measured for specific volume resistivity at  $25^{\circ}\text{C}$  in accordance with JIS C 2101.

(FALEX wear test)

The test oils were each applied to a test journal for measuring the amount of the test journal worn by having the journal run in at a test oil temperature of 100 °C under a load of 150 lb for 1 minute and then running it under a load of 250 lb for 2 hours in accordance with ASTM D 2670.

10

15

20

25

5

#### (Hygroscopicity)

Thirty grams (30 g) of each of the test oils were placed in a 300-ml beaker, allowed to stand for 7 days in an air-conditioned bath maintained at a temperature of 60  $^{\circ}$ C and a humidity of 30 % and then measured for water content by the Karl-Fischer method.

(Thermal and chemical stability)

Thermal and chemical stabilities of the test oils were evaluated by the following sealed tube test with HFC-134a in accordance with JIS K 2211 4.9.

An equi-volume mixture of each of the test oils and the refrigerant (HFC-134a) was sealed, together with copper, iron and aluminum catalysts, in a glass tube and then heated to 250°C for 168 hours to observe discoloration of the test oil and surface states of the catalysts and determine the degree of discoloration. The degree of discoloration of the

test oil was classified into 9 grades ranging from 0 (no discoloration) to 8 (black-brown color).

(Pour point)

5 The test oils are each measured for specific pour point in accordance with JIS K 2269.

10

15

20

15

5

10

Ω

Та

20

25

Pour point	9		17		-45	0 0	<b>-</b>	2 5	01	ı	 I	-	1	ı	ı		l	1 [	
		N1	No obongo	No change	No change	No change	No change	No change		1	ı	ı	ı	: 1	l i	: (	ı	1	
Sealed tube test	Catalysts	Fc	Inster decreed	No obergo	In cliange	Luster decreased	Inster decreased	No chango		ı	ı	ı	ı	ı	ı	ı	ı	ı	
Sealed		пე	No change	No change	No change	No change	No change	No change	C C	i	ı	ı	ı	ı	ı	ı	ı	ı	
	0i1	color	۶.	·	~ <b>~</b>	٠.	- <del>-</del>	· —	۱ ،	1	ı	J	1	ı	ı	ı	1	ı	
llygro-	60°C, 30%	9	0.19	18	10	0.13	0.19	0. 20	0.01	0,01	1.31	1.01	2, 30	181	. 1	ı	ı	1	
Falex test	journal	(mg)	26	26	22	92	25	25	23	25	40	35	38	30	- ; ,	ı	ı	ı	
Resistivity Falex test	(25°C)	(35.011)	4.0×1014	3.9×1014	1 × 10 14	4. 2×1014	3.8×1014	$3.8 \times 10^{14}$	3.8×1015	$6.4 \times 10^{15}$	$1.1 \times 10^{11}$	$1.2 \times 10^{11}$	5. 6×1010	4.8×1010	1	ı	ı	ı	
Miscibility with	IFC-134a	Temperature Range (°C)	-28~CT**	-28~CT**	27~CT**	-27~CT**	-32~CT**	-32~CT**	Immiscible	Immiscible	<-70~-97	<-70~56	V9~0L->	$-51 \sim 32$	Immiscible	Immiscible	Immiscible	lumiscible	
Kincmatic	(m <sup>2</sup> /s)	(c / mm)	8.1	8.1	6.2	6.2	11.5	11.5			4.9				6.1	4.9	5.4	4.4	
ds*	Amount	(Out #t %)	Ι	0.5	ı	0.5	ı	0.5	ı	ı	ı	1	i	1	1	ı	ı	ı	1
Epoxy	compounds*	Kind	None	t-BuPGE	None	PGE	None	s-BuPGE	None	None	None	None	None	None	None	None	None	None	
Base	oils		7	-	2	2	က	က	~	2	9	_	∞			11			
Examples	Comparative	Examples	Example 1	Example 2	Com. Ex. 1	Com. Ex. 2	Com. Ex. 3	Com. Ex. 4	Com. Ex. 5	Com. Ex. 6	Com. Ex. 7	Com. Ex. 8	Com. Ex. 9	Com. Ex. 10	Com. Ex. 11	Com. Ex. 12	Com. Ex. 13	Com. Ex. 14	

: Phenyl Glycidyl Ether 354 \*

; s-Butylphenyl Glycidyl Ether s-BuPGE

t-BuPGE : t-Butylphenyl Glycidyl Ether

\*\* CT; Critical temperature of IIFC-134a (102°C)

10

15

20

It is apparent from the results indicated in Table 1 that the refrigerator oils (Examples 1 and 2) according to the present invention are excellent in miscibility with a refrigerant, HFC-134a, as compared with those of Comparative Examples 5-6 and 11-14.

As is apparent from the results indicated in Table 1, the esters of Comparative Examples 11 and 13 in which the alkyl groups of the acid moiety are all straight-chain ones are inferior in miscibility with the refrigerant. Further, Table 1 shows that the esters of Comparative Examples 12 and 14 which have heretofore been used as lubricating oils, refrigerator oils and the like and in which the acid moiety is originated from a natural fat or oil, are also inferior in miscibility with the refrigerant.

Examples 7 and 8 as well as the polyoxypropylene glycols of Comparative Examples 9 and 10 are excellent in miscibility with the refrigerant, but these ethers and glycols are inferior in insulating property thereby rendering them unusable for hermetic type compressors. Still further, Table 1 shows that the ethers and glycols of Comparative Examples 7-10 have hygroscopicity 5-10 times that of the refrigerator oils of Examples 1 and 2 and are also inferior in electrical insulating property, ice choke, wear resistance, stability and the like to the refrigerator oils of the Examples.

10

15

20

25

The FALEX wear test shows that the refrigerator oils of Examples 1 and 2 are at least equal in wear resistance to those of Comparative Examples 7-10.

The esters of Comparative Examples 1-4 are at least equivalent to those of Examples 1 and 2 in miscibility with HFC-134a, insulating property, wear resistance and hygroscopicity, but, as is apparent from the results indicated in Table 1 that the refrigerator oils (Examples 1 and 2) according to the present invention is excellent in thermal stability having low pour point as compared with those of Comparative Examples 1-4.

The results of the sealed tube test shows that the refrigerator oils of Example 2 is still more excellent in thermal and chemical stability as compared with the refrigerator oil of Example 1 as well as the refrigerator oils of Comparative Examples 1 and 3.

#### (Effect of the Invention)

As is apparent from the above comparative experiments, the refrigerator oils according to the present invention are suitable for use in refrigerators using therein a hydrogen-containing halogenocarbon as a refrigerant and are excellent in electrical insulating property, wear resistance, nonhygroscopicity and thermal and chemical stability. In other words, the refrigerator oils according to the present invention excellently have all properties which are important for refrigerator oils.

#### What is claimed is:

1. A fluid composition for a refrigerator, which comprises a chlorine-free fluorocarbon refrigerant and a refrigerator oil, said refrigerator oil consisting essentially of a tetraester of pentaerythritol of formula (1)

$$\begin{array}{c} CH_2OH \\ HOH_2C - \overset{1}{C} - CH_2OH \\ CH_2OH \end{array} \tag{1}$$

10

5

with both 2-ethylhexanoic acid and 3.5.5-trimethylhexanoic acid, said refrigerator oil exhibiting a pour point not higher than  $-10^{\circ}$ C.

15

- 2. The fluid composition according to claim 1 wherein said refrigerator oil has a pour point of -20  $^{\rm o}{\rm C}$  to  $80^{\rm o}{\rm C}$  .
- 3. The fluid composition according to claim 1 wherein said 2-ethylhexanoic acid and 3.5.5-trimethylhexanoic acid are in a molar ratio of 1:1.

20

25

4. The fluid composition according to claim 1 which additionally contains 0.1-5% by weight based on the total amount of said refrigerator oil of at least one epoxy compound, said epoxy compound being a member selected from the group consisting of phenylglycidyl ether epoxy compounds, alkylphenylglycidyl ether epoxy compounds, alkylglycidyl ether epoxy compounds, glycidyl ester epoxy compounds, alkyloxirane compounds, alkyloxirane compounds,

10

15

20

25

alicyclic epoxy compounds and epoxidized fatty acid monoesters.

- 5. The fluid composition according to claim 1 which additionally contains at least one phosphorus compound selected from the group consisting of phosphoric esters, acid phosphoric esters, amine salts of acid phosphoric esters, chlorinated phosphoric esters, and phosphorous esters.
- 6. The fluid composition according to claim 1 which additionally contains at least one additive selected from the group consisting of phenol antioxidants, amine antioxidants, wear resistant additives, extreme pressure agents, oiliness improvers, antiforming agents and metal inactivators.
- 7. A fluid composition for a refrigerator, which consists of a chlorine-free fluorocarbon refrigerant and 1-500 parts by weight based on 100 parts by weight of said refrigerant of a refrigerator oil, said refrigerator oil being a tetraester of pentaerythritol of formula (1)

$$\begin{array}{c} CH_2OH \\ HOH_2C - \overset{1}{C} - CH_2OH \\ CH_2OH \end{array} \tag{1}$$

with both 2-ethylhexanoic acid and 3,5,5-trimethylhexanoic acid, said refrigerator oil exhibiting a pour point not higher than  $-10^{6}$ C.

25

5

8. A fluid composition for a refrigerator, which consists of a chlorine-free fluorocarbon refrigerant and 1-500 parts by weight based on 100 parts by weight of said refrigerant of a refrigerator oil, said refrigerator oil consisting of a tetraester of pentaerythritol of formula (1)

$$\begin{array}{c} CH_2OH \\ HOH_2C - \overset{I}{C} - CH_2OH \\ CH_2OH \end{array} \tag{1}$$

with both 2-ethylhexanoic acid and 3,5,5-trimethylhexanoic acid; and 0.1-5% by weight based on the total amount of said refrigerator oil of at least one epoxy compound selected from the group consisting of phenylglycidyl ether epoxy compounds, alkylphenylglycidyl ether epoxy compounds, alkylphenylglycidyl ether epoxy compounds, alkylglycidyl ether epoxy compounds, glycidyl ester cpoxy compounds, allyloxirane compounds, alkyloxirane compounds, alicyclic epoxy compounds and epoxidized fatty acid monoesters and said refrigerator oil exhibiting a pour point not higher than -10°C.

9. A fluid composition for a refrigerator, which consists of a chlorine-free fluorocarbon refrigerant and 1-500 parts by weight based on 100 parts by weight of said refrigerant of a refrigerator oil, said refrigerator oil consisting of as a major component a tetraester of pentaerythritol of formula (1)

$$\begin{array}{c} CH_2OH \\ HOH_2C - \overset{|}{C} - CH_2OH \\ CH_2OH \end{array} \tag{1}$$

with both 2-ethylhexanoic acid and 3,5,5-trimethylhexanoic acid; and at least one conventional oil selected from the group consisting of paraffinic mineral oils, naphthenic mineral oils, poly $\alpha$ -olefins and alkylbenzenes and said refrigerator oil exhibiting a pour point not higher than  $-10^{\circ}\mathrm{C}$ .

10. A fluid composition for a refrigerator, which consists of a chlorine-free fluorocarbon refrigerant and 1-500 parts by weight based on 100 parts by weight of said refrigerant of a refrigerator oil, said refrigerator oil consisting of a tetraester of pentaerythritol of formula (1)

$$\begin{array}{c} CH_2OH \\ HOH_2C - \overset{|}{C} - CH_2OH \\ CH_2OH \end{array} \tag{1}$$

15

10

5

with both 2-ethylhexanoic acid and 3,5,5-trimethylhexanoic acid; and 0.1-5.0 % by weight based on the total amount of said refrigerator oil of at least one phosphorus compound selected from the group consisting of phosphoric esters, acid phosphoric esters, amine salts of acid phosphoric esters, chlorinated phosphoric esters, and phosphorous esters and said refrigerator oil exhibiting a pour point not higher than  $-10^{\circ}\mathrm{C}$ .

25

20

11. A fluid composition for a refrigerator, which consists of a chlorine-free fluorocarbon refrigerant and 1-500 parts by weight based on 100 parts by weight of said

10

15

20

25

refrigerant of a refrigerator oil, said refrigerator oil consisting of a tetraester of pentaerythritol of formula (1)

$$\begin{array}{c} CH_2OH \\ HOH_2C - \overset{|}{C} - CH_2OH \\ CH_2OH \end{array} \tag{1}$$

with both 2-ethylhexanoic acid and 3,5,5-trimethylhexanoic acid; and not more than 10% by weight of at least one additive selected from the group consisting of phenol antioxidants, amine antioxidants, wear resistant additives, extreme pressure agents, oiliness improvers, antifoaming agents and metal inactivators and said refrigerator oil exhibiting a pour point not higher than -10°C.

12. A fluid composition for a refrigerator, which consists of a chlorine-free fluorocarbon refrigerant and 1-500 parts by weight based on 100 parts by weight of said refrigerant of a refrigerator oil, said refrigerator oil consisting of as a major component a tetraester of pentaerythritol of formula (1)

$$\begin{array}{c} CH_2OH \\ HOH_2C - \overset{1}{C} - CH_2OH \\ CH_2OH \end{array} \tag{1}$$

with both 2-ethylhexanoic acid and 3,5,5-trimethylhexanoic acid; at least one conventional oil selected from the group consisting of paraffinic mineral oils, naphthenic mineral oils, poly $\alpha$ -olefins and alkylbenzenes; and 0.1-5% by weight

based on the total amount of said refrigerator oil of at least one epoxy compound, said epoxy compound being a member selected from the group consisting of phenylglycidyl ether epoxy compounds, alkylphenylglycidyl ether epoxy compounds, alkylglycidyl ether epoxy compounds, glycidyl ester epoxy compounds, alkyloxirane compounds, alkyloxirane compounds, alkyloxirane compounds, alicyclic epoxy compounds and epoxidized fatty acid monoesters and said refrigerator oil exhibiting a pour point not higher than  $-10^{\circ}$ C.

10

5

13. A fluid composition for a refrigerator, which consists of a chlorine-free fluorocarbon refrigerant and 1-500 parts by weight based on 100 parts by weight of said refrigerant of a refrigerator oil, said refrigerator oil being a tetraester of pentaerythritol of formula (1)

15

$$\begin{array}{c} CH_2OH \\ HOH_2C - \overset{|}{C} - CH_2OH \\ CH_2OH \end{array} \tag{1}$$

20

25

with both 2-ethylhexanoic acid and 3,5,5-trimethylhexanoic acid; 0.1-5% by weight based on the total amount of said refrigerator oil of at least one epoxy compound, said epoxy compound being a member selected from the group consisting of phenylglycidyl ether epoxy compounds, alkylphenylglycidyl ether epoxy compounds, alkylphenylglycidyl ether epoxy compounds, glycidyl ester epoxy compounds, allyloxirane compounds, alkyloxirane compounds, alkyloxirane compounds, alkyloxirane compounds, alicyclic epoxy compounds and epoxidized fatty acid monoesters; and 0.1-5.0 % by weight

10

15

20

25

based on the total amount of said refrigerator oil of at least one phosphorus compound selected from the group consisting of phosphoric esters, acid phosphoric esters, amine salts of acid phosphoric esters, chlorinated phosphoric esters, and phosphorous esters and said refrigerator oil exhibiting a pour point not higher than  $-10^{\circ}$ C.

14. A fluid composition for a refrigerator, which consists of a chlorine-free fluorocarbon refrigerant and 1-500 parts by weight based on 100 parts by weight of said refrigerant of a refrigerator oil, said refrigerator oil being a tetraester of pentaerythritol of formula (1)

$$\begin{array}{c} CH_2OH \\ HOH_2C - \overset{|}{C} - CH_2OH \\ CH_2OH \end{array} \tag{1}$$

with both 2-ethylhexanoic acid and 3,5,5-trimethylhexanoic acid; 0.1-5.0 % by weight based on the total amount of said refrigerator oil of at least one phosphorus compound selected from the group consisting of phosphoric esters, acid phosphoric esters, amine salts of acid phosphoric esters, chlorinated phosphoric esters, and phosphorous esters; and not more than 10% by weight of at least one additive selected from the group consisting of phenol antioxidants, amine antioxidants, wear resistant additives, extreme pressure agents, oiliness improvers, antifoaming

10

15

20

25

agents and metal inactivators and said refrigerator oil exhibiting a pour point not higher than  $-10^{\circ}$ C.

15. A fluid composition for a refrigerator, which consists of a chlorine-free fluorocarbon refrigerant and 1-500 parts by weight based on 100 parts by weight of said refrigerant of a refrigerator oil, said refrigerator oil consisting of as a major component a tetraester of pentaerythritol of formula (1)

$$\begin{array}{c} CH_2OH \\ HOH_2C - \overset{\text{!`}}{C} - CH_2OH \\ CH_2OH \end{array} \tag{1}$$

with both 2-ethylhexanoic acid and 3,5,5-trimethylhexanoic acid; at least one conventional oil selected from the group consisting of paraffinic mineral oils, naphthenic mineral oils, poly $\alpha$ -olefins and alkylbenzenes; and 0.1-5.0 % by weight based on the total amount of said refrigerator oil of at least one phosphorus compound selected from the group consisting of phosphoric esters, acid phosphoric esters, amine salts of acid phosphoric esters, chlorinated phosphoric esters, and phosphorous esters and said refrigerator oil exhibiting a pour point not higher than  $-10^{6}$ C.

16. A fluid composition for a refrigerator, which consists of a chlorine-free fluorocarbon refrigerant and 1-500 parts by weight based on 100 parts by weight of said

10

15

20

25

refrigerant of a refrigerator oil, said refrigerator oil being a tetraester of pentaerythritol of formula (1)

$$\begin{array}{c} CH_2OH \\ HOH_2C - \overset{!}{C} - CH_2OH \\ & CH_2OH \end{array} \tag{1}$$

with both 2-ethylhexanoic acid and 3,5,5-trimethylhexanoic acid; 0.1-5% by weight based on the total amount of said refrigerator oil of at least one epoxy compound, said epoxy compound being a member selected from the group consisting of phenylglycidyl ether epoxy compounds, alkylphenylglycidyl ether epoxy compounds, alkylglycidyl ether epoxy compounds, glycidyl ester epoxy compounds, allyloxirane compounds, alkyloxirane compounds, alkyloxirane compounds, alkyloxirane compounds and epoxidized fatty acid monoesters; and not more than 10% by weight of at least one additive selected from the group consisting of phenol antioxidants, amine antioxidants, wear resistant additives, extreme pressure agents, oiliness improvers, antifoaming agents and metal inactivators and said refrigerator oil exhibiting a pour point not higher than -10°C.

17. A fluid composition for a refrigerator, which consists of a chlorine-free fluorocarbon refrigerant and 1-500 parts by weight based on 100 parts by weight of said refrigerant of a refrigerator oil, said refrigerator oil consisting of as a major component a tetraester of pentaerythritol of formula (1)

10

15

$$CH2OH$$

$$HOH2C - C - CH2OH$$

$$CH2OH$$

$$(1)$$

with both 2-ethylhexanoic acid and 3,5,5-trimethylhexanoic acid; at least one conventional oil selected from the group consisting of paraffinic mineral oils, naphthenic mineral oils, poly $\alpha$ -olefins and alkylbenzenes; and not more than 10% by weight of at least one additive selected from the group consisting of phenol antioxidants, amine antioxidants, wear resistant additives, extreme pressure agents, oiliness improvers, antifoaming agents and metal inactivators and said refrigerator oil exhibiting a pour point not higher than  $-10^{\circ}$ C.

18. A fluid composition for a refrigerator, which consists of a chlorine-free fluorocarbon refrigerant and 1-500 parts by weight based on 100 parts by weight of said refrigerant of a refrigerator oil, said refrigerator oil consisting of as a major component a tetraester of pentaerythritol of formula (1)

20

25

$$\begin{array}{c} CH_2OH \\ HOH_2C - \overset{1}{C} - CH_2OH \\ CH_2OH \end{array} \tag{1}$$

with both 2-ethylhexanoic acid and 3,5,5-trimethylhexanoic acid; at least one conventional oil selected from the group consisting of paraffinic mineral oils, naphthenic mineral oils, poly $\alpha$ -olefins and alkylbenzenes; 0.1-5% by weight

10

15

20

25

based on the total amount of said refrigerator oil of at least one epoxy compound, said epoxy compound being a member selected from the group consisting of phenylglycidyl ether epoxy compounds, alkylphenylglycidyl ether epoxy compounds, alkylglycidyl ether epoxy compounds, glycidyl ester epoxy compounds, allyloxirane compounds, alkyloxirane compounds, alicyclic epoxy compounds and epoxidized fatty acid monoesters; and 0.1-5.0 % by weight based on the total amount of said refrigerator oil of at least one phosphorus compound selected from the group consisting of phosphoric esters, acid phosphoric esters, amine salts of acid phosphoric esters, chlorinated phosphoric esters, and phosphorous esters and said refrigerator oil exhibiting a pour point not higher than -10°C.

19. A fluid composition for a refrigerator, which consists of a chlorine-free fluorocarbon refrigerant and 1-500 parts by weight based on 100 parts by weight of said refrigerant of a refrigerator oil, said refrigerator oil consisting of a tetraester of pentaerythritol of formula (1)

 $\begin{array}{c} CH_2OH \\ HOH_2C - \overset{1}{C} - CH_2OH \\ CH_2OH \end{array} \tag{1}$ 

with both 2-ethylhexanoic acid and 3,5,5-trimethylhexanoic acid; at least one conventional oil selected from the group consisting of paraffinic mineral oils, naphthenic mineral oils, poly $\alpha$ -olefins and alkylbenzenes; 0.1-5.0 % by weight

10

based on the total amount of said refrigerator oil of at least one phosphorus compound selected from the group consisting of phosphoric esters, acid phosphoric esters, amine salts of acid phosphoric esters, chlorinated phosphoric esters, and phosphorous esters; and not more than 10% by weight of at least one additive selected from the group consisting of phenol antioxidants, amine antioxidants, wear resistant additives, extreme pressure agents, oiliness improvers, antifoaming agents and metal inactivators and said refrigerator oil exhibiting a pour point not higher than  $-10^{\circ}$ C.

20. A fluid composition for a refrigerator, which consists of a chlorine-free fluorocarbon refrigerant and 1-500 parts by weight based on 100 parts by weight of said refrigerant of a refrigerator oil, said refrigerator oil consisting of a tetraester of pentaerythritol of formula (1)

$$CH2OH$$

$$HOH2C - C - CH2OH$$

$$CH2OH$$
(1)

20

25

15

with both 2-ethylhexanoic acid and 3,5,5-trimethylhexanoic acid; 0.1-5% by weight based on the total amount of said refrigerator oil of at least one epoxy compound, said epoxy compound being a member selected from the group consisting of phenylglycidyl ether epoxy compounds, alkylphenylglycidyl ether epoxy compounds, alkylglycidyl ether epoxy compounds, glycidyl ester epoxy compounds, allyloxirane compounds,

10

15

alkyloxirane compounds, alicyclic epoxy compounds and epoxidized fatty acid monoesters; 0.1-5.0 % by weight based on the total amount of said refrigerator oil of at least one phosphorus compound selected from the group consisting of phosphoric esters, acid phosphoric esters, amine salts of acid phosphoric esters, chlorinated phosphoric esters, and phosphorous esters; and not more than 10% by weight of at least one additive selected from the group consisting of phenol antioxidants, amine antioxidants, wear resistant additives, extreme pressure agents, oiliness improvers, antifoaming agents and metal inactivators and said refrigerator oil exhibiting a pour point not higher than -10°C.

21. A fluid composition for a refrigerator, which consists of a chlorine-free fluorocarbon refrigerant and 1-500 parts by weight based on 100 parts by weight of said refrigerant of a refrigerator oil, said refrigerator oil consisting of as a major component a tetraester of pentaerythritol of formula (1)

20

25

$$\begin{array}{c} CH_2OH \\ HOH_2C - \overset{1}{C} - CH_2OH \\ CH_2OH \end{array} \tag{1.}$$

with both 2-ethylhexanoic acid and 3.5.5-trimethylhexanoic acid; at least one conventional oil selected from the group consisting of paraffinic mineral oils, naphthenic mineral oils, poly $\alpha$ -olefins and alkylbenzenes; 0.1-5% by weight

10

based on the total amount of said refrigerator oil of at least one epoxy compound, said epoxy compound being a member selected from the group consisting of phenylglycidyl ether epoxy compounds, alkylphenylglycidyl ether epoxy compounds, alkylglycidyl ether epoxy compounds, glycidyl ester epoxy compounds, allyloxirane compounds, alkyloxirane compounds, alicyclic epoxy compounds and epoxidized fatty acid monoesters; and not more than 10% by weight of at least one additive selected from the group consisting of phenol antioxidants, amine antioxidants, wear resistant additives, extreme pressure agents, oiliness improvers, antifoaming agents and metal inactivators and said refrigerator oil exhibiting a pour point not higher than  $-10^{\circ}$ C.

A fluid composition for a refrigerator, which consists of a chlorine-free fluorocarbon refrigerant and 1-500 parts by weight based on 100 parts by weight of said refrigerant of a refrigerator oil, said refrigerator oil consisting of as a major component a tetraester of pentaerythritol of formula (1)

(1)

CH<sub>2</sub>OH  $HOH_2C - \overset{|}{C} - CH_2OH$ 

with both 2-ethylhexanoic acid and 3,5,5-trimethylhexanoic acid; at least one conventional oil selected from the group consisting of paraffinic mineral oils, naphthenic mineral oils, poly $\alpha$ -olefins and alkylbenzenes; 0.1-5 % by weight

20

25

based on the total amount of said refrigerator oil of at least one epoxy compound, said epoxy compound being a member selected from the group consisting of phenylglycidyl ether epoxy compounds, alkylphenylglycidyl ether epoxy compounds, alkylglycidyl ether epoxy compounds, glycidyl ester epoxy compounds, allyloxirane compounds, alkyloxirane compounds, alicyclic epoxy compounds and epoxidized fatty acid monoesters; 0.1-5.0 % by weight based on the total amount of said refrigerator oil of at least one phosphorus compound selected from the group consisting of phosphoric esters, acid phosphoric esters, amine salts of acid phosphoric esters, chlorinated phosphoric esters, and phosphorous esters; and not more than 10% by weight of at least one additive selected from the group consisting of phenol antioxidants, amine antioxidants, wear resistant additives, extreme pressure agents, oiliness improvers, antifoaming agents and metal inactivators and said refrigerator oil exhibiting a pour point not higher than  $-10^{0}$ C.

20

5

10

10

15

#### ABSTRACT OF THE DISCLOSURE

A fluid composition for a refrigerator, which comprises a chlorine-free fluorocarbon refrigerant and a refrigerator oil, said refrigerator oil consisting essentially of a tetraester of pentaerythritol of formula (1)

$$\begin{array}{c} CH_2OH \\ HOH_2C - \overset{|}{C} - CH_2OH \\ CH_2OH \end{array} \tag{1}$$

with both 2-ethylhexanoic acid and 3,5,5-trimethylhexanoic acid, said refrigerator oil exhibiting a pour point not higher than  $-10^{\circ}$ C.

20

### Declaration, Power of Attorney, and Petition

As a below named inventor, I hereby declare that:

Page 1 of 2

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled FLUID COMPOSITIONS CONTAINING REFRIGERATOR OILS AND CHLORINE—FREE FLUOROCARBON REFRIGERANTS

the specification of which (check one) 

| Signature | Application | Ap

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, § 1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code § 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

### Prior Foreign Application(s)

Hei. 1-341244	Inna	D 1 00 1000	Priority	claimed
(ynmpet)	Japan (Country)	December 28, 1989		
	(Country)	Duy/month/year filed	Yes	No
Hei. 1-341245	Japan	December 28, 1989	$\boxtimes$	
(Numer)	(Country)	Day/month/year filed	Yes	No
Hei, 2-105772	Japan .	April 20, 1990	$\boxtimes$	
(Number)	(Country)	Day/month/year filed	Yes	No
Hei2-121133	Japan	Mary 15 1000		
(Number)	(Country)	May 15, 1990 Day/month/year filed	X	Ü
I harabu alaim tha hara	Character Title 16 to 10 to 10 to 10		Yes	No

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, § 1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

(Application Secial No.) (Filing date) (Status) (patented, pending, abandoned)

(Application Secial No.) (Filing date) (Status) (patented, pending, abandoned)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

And I hereby appoint

Ralph E. Bucknam, Reg. No. 14,814, Fernanda M. Fiordalisi, Reg. No. 20,938, of BUCKNAM AND ARCHER, Joseph J. Orlando, Reg. No. 25,218 600 Old Country Road, Garden City, New York 11530 - Tel. No. (516) 222-8885

my attorney with full power of substitution and revocation, to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith.

Wherefore I pray that Letters Patent be granted to me for the invention or discovery described and claimed in the foregoing specification and claims, and I hereby subscribe my name to the foregoing specification and claims, declaration, power of attorney, and this petition.

Full name of sole or first inventor Hiroshi HASEGAWA Inventor's signature Missiski Hasegawa	
Inventor's signature diroski Hasegawa	Date Innsch 3, 1998
Residence C/O NIPPON OIL CO., LID., CENTRAL TECH	NICAL RESEARCH LABORATORY
Citizenship JAPAN 8, Chidori-cho, Naka-	ku, Yokohama-shi, Kanagawa,JAPAN
Post Office Address Same as residence	
Full name of second joint inventor, if any Noboru ISHIDI	<u> </u>
Full name of second joint inventor, if any	Date March 3rd 1998
Residence C/O NIPPON OIL CO., LTD., CENTRAL FECHI	NICAL RESEARCH LABORATORY
Citizenship JAPAN 8, Chidori-cho, Naka-l Post Office Address Same as residence	ku, Yokohama-shi, Kanagawa, JAPAN

## Declaration, Power of Attorney, and Petition

As a below named inventor, I hereby	declare that:			Page	2 of 2
My residence, post office address	and citizenship are as s	tated below next to my n	ame,		
I believe I am the original, first ar inventor (if plural names are listed below tion entitled FLUID COMPOSITIONS REFRIGERANTS	) of the subject matter wh	ich is claimed and for which	n a patent is s	ought on	the inven-
				cification	of which
(check one) (2) is attached hereto.	was filed on		as	<i>.</i>	
Application Serial No.	and was am	ended on	•••••••••	(11 ap	oplicable).
I hereby state that I have reviewed claims, as amended by any amendmen	and understand the control treferred to above.	ntents of the above identif	ied specifica	tion, inc	luding the
I acknowledge the duty to discle accordance with Title 37, Code of Fed	ose information which eral Regulations, § 1.56	is material to the exam (a).	ination of t	his appl	ication in
I hereby claim foreign priority ber patent or inventor's certificate listed bel certificate having a filing date before the	low and have also identil	ied below any foreign app	lication for r	applica patent or	tion(s) for inventor's
	Prior Foreign Ap	plication(s)			
Hei. 1-341244	Japan	December	28 1989	Priority	claimed
(Number)	(Country)		onth/year filed	∑ Yes	∐ No
Hei. 1-341245	Japan	December	28, 1989	<b>Z</b>	
(Number)	(Country)		onth/year filed	Yes	No
Hei 2-105772 (Number)	Japan (Country)	April 20,	Onth/year filed	⊠ Yes	□ No
Hei. 2-121133	Japan	May 15, 1	990	<b>⊠</b>	
(Number) I hereby claim the benefit under Ti	(Country)	- Duy/mo	onth/year filed	Yes	No
TApplication Serial No.] (Filing date)  [Application Serial No.] (Filing date)			•••••	••••	ing, abandoned)
I hereby declare that all statement information and belief are believed to willful false statements and the like so m 18 of the United States Code and that spatent issued thereon.	be true; and further than ade are punishable by fi	at these statements were in ne or imprisonment, or bo	id that all st made with th oth, under Se	atements ne know ection 10	s made on ledge that 01 of Title
And I hereby appoint					
	ARCHER, Josep oad, Garden City, Ne	nanda M. Fiordalisi, R h J. Orlando, I w York 11530 -			218
my attorney with full power of substitu the Patent and Trademark Office conn		prosecute this application	and to tran	sact all b	usiness in
Wherefore I pray that Letters Pate foregoing specification and claims, a declaration, power of attorney, and this	nd I hereby subscribe				
Inventor's signature	, LTD., CENTRAL T	I ECHNICAL RESEARCH ka-ku, Yokohama-sh	Date My LABORATO li, Kanag		1998 PAN
Full name of second joint inventor, if a	18 y	SHIKAWA	Date 716	nch .	
Second Inventor's signature Tal. Residence C/O NIPPON OIL	LTD., CENTRAL TE	CHNICAL RESEARCH	LABORATOR	Y	
Citizenship JAPAN 8	Chidori-cho, Nak	a-ku, Yokohama-sh	i, Kanaga	wa, JA	YPAN

## United States Patent & Trademark Office

Office of Initial Patent Examination -- Scanning Division



Application deficiencies found during scanning:

1.	Application papers are not suitable for scanning and are not in compliance with 37 CTR 1	_
	because:	
	☐ All sheets must be the same size and either A4 (21 cm x 29.7 cm) or 8-1/2"x 11".	•
	Pages do not meet these requirements.	
	Papers are not flexible, strong, smooth, non-shiny, durable, and white.	
	Papers are not typewritten or mechanically printed in permanent ink on one side.	
	Papers contain improper margins. Each sheet must have a left margin of at least	
	2.5 cm (1") and top, bottom and right margins of at least 2.0 cm (3/4").	
	Papers contain hand lettering.	
	_ 1 upot 0 comuni minte concernige	
2	Drawings are not in compliance and were not scanned because:	
<b>-</b> .	☐ The drawings or copy of drawings are not suitable for electronic reproduction.	
	All drawings sheets are not the same size. Pages must be either A4 (21 cm x 29.7 cm)	
	or 8-1/2" x 11".	
	☐ Each sheet must include a top and left margin of at least 2.5 cm (1"), a right margin of	
	at least 1.5 cm (9/16") and a bottom margin of at least 1.0 cm (3/8").	
	<b>3</b>	
3.	Page(s) are not of sufficient clarity, contrast and quality for electronic	ic
	reproduction.	
	·	
4.	Page(s) are missing.	
	11	
5.	OTHER: NO DRAWINGS	_